



#8/a
Hawkins
11/6/02

06097.P019

Patent

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Application of:

Roland Weitkamp

Serial No.: 09/802,044

Filed: March 7, 2001

For: CONTROL SYSTEM FOR A WIND
POWER PLANT

)
) Art Unit: 2834
)
)
) Examiner: J. Waks
)
)
)
)
)
)

RECEIVED
NOV - 4 2002
TECHNOLOGY CENTER 2800

AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

In response to the Office Action mailed April 30, 2002, Applicant respectfully requests the Examiner to enter the following amendments and consider the following remarks:

"Express Mail" mailing label number: EL821776905US
Date of Deposit: October 30, 2002
I hereby certify that I am causing this paper or fee to be deposited with the United States Postal Service "Express Mail Post Office to Addressee" service on the date indicated above and that this paper or fee has been addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231
Deborah A. McGovern
(Typed or printed name of person mailing paper or fee)
Deborah A. McGovern
(Signature of person mailing paper or fee)
October 30, 2002
(Date signed)

In the Specification

Please replace the paragraphs on pages 2-11 starting at the Summary of the Invention paragraph with the following paragraphs.

SUMMARY OF THE INVENTION

a!
cont.

The above outlined known approach of reducing the power output in case of high wind velocities makes it possible -e.g. in a variable-speed pitch plant with a control algorithm for controlling the rotor speed on the basis of the pitch angle averaged over time to obtain very high ratios between the rotor diameter and the generator performance without an accompanying increase of component fatigue as compared to conventionally designed turbines. A rating of 330 to 280 W/m² can be obtained and is economically reasonable especially at inland locations.

For reasons of safety, the design of the towers of wind power plants is on principle determined on the basis of very unfavorable assumptions (e.g. high wind turbulences and maximum wind distribution in the designed wind zone); therefore, in the majority of locations, considerable safety margins of the power output are left unused in the turbines. Thus, the problem exists how these normally existing safety margins can be utilized for improving the efficiency of the turbine.

According to an embodiment of the invention, this problem is solved by performing, by means of an already existing or additionally installed sensor arrangement with connected signal processing system in the wind power plant, a

a' cont.
direct or indirect quantification of the current turbine stresses. By comparison with allowable stresses (or correlating values) detected by computation or empirically, the turbine will be operated with a rotor speed and a power yield which are optimized under the economical aspect.

Other than in the normally used state of the art wherein the operational control process is provided to control the blade angle and/or the rotational speed according to fixed functions in dependence on power, blade angle or wind velocity, this novel control process is to be performed only to the extent required due to the local conditions or meteorological conditions at the respective point of time to thus obtain optimum efficiency.

A simple algorithm suited for the above purpose is based on the statistical evaluation of one, a plurality or all of the measurement values (e.g. rotor speed, generator performance, pitch angle, pitch rate, wind velocity and wind direction) mentioned among those operating data which are anyway continuously detected in many present day wind power plants (e.g. variable-speed pitch plants).
in the present context, the term "statistical evaluation" is meant to include at least the continuous detection of the minimum, maximum and average values and the standard deviation for a plurality of sliding time intervals Δt (30 s to 60 min.).
More-complex statistical evaluations of the operating data or the derivations thereof will result in a more successful control. Since wind is a stochastically distributed value, a reasonable detection and arithmetical representation of the measurement

ai
cont.

values can be performed only by means of distribution and probability functions or spectra. On the basis of measurements or simulation computations, the correlation coefficients of the statistical data relative to the local and meteorological conditions and the current stresses on the components can be determined with sufficient accuracy. For instance, the average pitch angle and the average rotor speed for a given turbine configuration are in direct relation to the average wind velocity; the standard deviation of the two former values allows for a conclusion on the turbulence intensity (gustiness) of the wind. Thus, besides the directly measured operating data, also important stress data (e.g. the blade bending moment and the thrust acting on the tower) can be statistically evaluated. These actual distributions of the stresses or of the values directly related thereto are compared to desired distribution functions which have been obtained by computation or empirically. These desired functions can be detected for each location as suited for the specific application and be stored in a data memory of the control system.

An example of an embodiment of the control system using the inventive control strategy will be explained in greater detail hereunder in connection with the accompanying drawing.

BRIEF DESCRIPTION OF THE DRAWING

The sole drawing is a block diagram of the control system using the control strategy according to an embodiment of the instant invention.

DESCRIPTION OF A PREFERRED EMBODIMENT

a!
cont.

In the block diagram, angular boxes are meant to represent signal processing systems or computing modules of a larger software package installed in a signal processing system. Laterally rounded boxes represent input data for the control system, irrespective of whether these data are measured on the turbine or supplied from an external source. Boxes curved on top and bottom represent data stores containing all data which are required for the execution of the control algorithm and are made available through the internal data detection or analysis, or are supplied from external data sources. Elements represented in solid lines are absolutely required for the control system; elements represented in dotted lines are optional components which improve the function of the control system and thus allow for a higher energy yield even though they will cause an increasing complexity of the control concept.

Schematically shown to the left of the vertical dash-dotted line in the left: half of the drawing is a schematic representation of the control systems used according to the state of the art. The input values 102 are the operating values provided to be permanently detected by the measurement sensors, such as the rotor and generator speeds n_R and n_G , respectively, the electrical power P_{el} , the generator torque M_G , the blade or pitch angle ϑ and the pitch rate $\dot{\vartheta}$, and the wind velocity v_w

a!
cont.

and the wind direction v_{dir} . On the basis of these measurement values, the turbine is controlled according to an algorithm implemented in the main computer 104 for operating the plant (standard control) 104. The regulated quantities are the pitch angle ϑ 105 and/or the generator moment M_{GSoll} 106 (e.g. also by selection of the generator stage in asynchronous turbines with switchable polarity). The control loop wherein, by means of the actuators, the desired values are turned into actual values which then will be detected as operational values to be used as control input values as schematically indicated, has been omitted from the block diagram for better survey.

According to the state of the art, additional measurement values (e.g. temperatures, hydraulic pressures, tower head accelerations, oil level and wear indications) allow for the detection of certain conditions of the plant and, if required, will result in shut-down of the turbine.

In the control system, the operating data are subjected to a statistical data pick-up 108 and are stored as spectra or distributions in a data store. Optionally, in the so-called loading model 110, the statistical operating data are converted 112 into statistical stress data by means of the correlation functions obtained in the simulation computations.

More-complex algorithms are based on additional measurement values which are more closely related to the stresses, and such algorithms allow for a distinctly

a!
cont.

more precise detection of the existing distribution of stresses and thus for a closer approach to the limiting values dictated by the respective design, thus obviating the need for the safety margins necessitated in simple algorithms.

The sensors on the turbine can be provided, Inter alia, as acceleration sensors on the tower head and the rotor blades, and/or wire strain gauges on representative points of the support structure (e.g. on the blade roots, rotor shaft, base of the tower).

By inclusion of additional wind-field data 114 which in the ideal case characterize the undisturbed onflow before the rotor, the control behavior can be considerably improved. Generally, for this purpose, use can be made of laser-optical and/or acoustic (ultrasonic) measuring methods which are suited both for measurements on individual points in the wind field and for measurements of complete wind profiles or wind fields in the rotor plane or also far before the rotor plane. A further improvement of the control behavior is accomplished by linking the control systems of the different turbines 116 of a wind park to each other; the considerably enlarged data base obtained in this manner will safeguard a faster but still statistically reliable response of the control systems.

All of the detected spectra or distributions will be stored, preferably classified according to operating year, average wind velocity and turbulence intensity.

Upon sufficiently accurate determination of the stresses through detection of stress data, it appears reasonable to transform the stress changes into so called

a
cmt.

Markov matrices by use of known counting methods or on the basis of the average values (online rainflow counting). To this end, microchips which have already entered the stage of industrial production are available from the field of aviation and space technology.

The actual distributions 112 which have been measured or have been computed from the measurement data are compared to the desired distributions 118 of the same values. For this purpose, data on design, planning and financing 120 are externally collected 122, input into the system and stored in a data store 124. Using an economy model 126, the desired distributions are derived from these data 120. Design data include e.g. the allowable loading distributions for the individual components; an example of the planning data is the expected wind distribution at the location; and the financing data include, in addition to the overall project costs, the current credit costs, the energy profits required according to the financing plan, and the current charges for power supply. Monthly updates 124 of these data per remote monitoring can be used for immediate adaptation of the control system to changes of the basic conditions, e.g. to changes of the charges for power supply or of the financing costs, new recognitions on the allowable stresses on the components, or even improved control algorithms. Data on the supra regional annual wind distribution make it possible, on the one hand, by comparison with the measured wind distribution at the location, to perform a correction of the planning data; on the other hand, in less favorable wind years, the turbine can be operated by use of a

"sharper" power characteristic curve for keeping up with the requirements of the financing plan.

a!
cont.

In the operating level control unit 128, the thus obtained desired distributions 118 are compared with the actual distributions 112. This way, the optimum operating level under the current meteorological and local conditions is computed. The regulated quantities ϑ_{opt} (blade angle) 130 and M_{Gopt} 132 and n_{Gopt} 134 (generator moment and generator speed, respectively) are to be understood as preset average values while, on the other hand, the current desired values supplied by the standard control system for adjustment to wind turbulences may temporarily deviate from these average values.

With the availability of such a control system, it may be advisable to operate the turbine with higher power yield in the first years of operation in order to lower the financing costs as quickly as possible, whereas, in later years, a low stress operation with reduced energy yield and a resultant lengthened lifespan may be considered optimum under the economic aspect.

In the ideal case, the above described control system is improved by the feature of an on-line detection of the current energy generating costs (Cost Of Energy COE) 136. For this purpose, it is required that the loading model 110 is combined, downstream thereof, with a stress model 111 for the individual components of the plant (a restriction to the main components, i.e. the rotor blades,

a!
cont.

the transmission, the generator, the converter and the tower will be sufficiently accurate), and with a damage model 138. The stress model 111 transforms the loading distributions into stress distributions on representative points of the components and is based on the methods applied in the design of the components. The results from finite element calculations can be summarized e.g. by consideration of merely a small number of compliance factors for some critical points. The damage model 138 compares the existing loading influences (e.g. Woehler lines) and thus computes the current component damage. (The damage of a component permits conclusions on the remaining lifespan). Therefore, the damage model 138 has to rely on a data base of the material or component behavior which is made available from an external source 122 and should be of a modular type so as to be adaptable to the most up-to-date recognitions (e.g. Woehler tests on original components, practical experiences from the serial production) in the course of the lifespan of the turbine. Since, in the present state of the art, particularly the material behavior has to be estimated on a very conservative basis due to lack of a sufficient data basis, the above adaptation feature offers a wide potential for yield increase.

If the damage model 138 has been suitably refined to allow for an online calculation of the damage and thus also of the damage rate for the important main components, the results of such calculation can be easily used for determining an equivalent damage rate for the whole turbine (Equivalent Damage Rate, EDR). The equivalent damage rate (unit: US\$/h) is a measure for the costs per time unit

a!
cont.

incurred by damage in the current operating condition of the turbine. The current energy generating costs can then be obtained by dividing the sum of the EDR and the other operating costs by the current power fed into the grid.

On this ideally refined level of the control strategy wherein the economical efficiency of the wind turbine is reduced to the decisive characteristic factor "cost of energy COE", the efficiency model has to be adapted to determine, as a value for comparison to the current COE, the maximum allowable COE where the turbine is still allowed to be operated. Should the current COE values 112 be too high in situations with weak winds, the turbine will be taken off the grid. Should the current COE values 112 be too high in situations with high wind velocities, the operating level control unit will lower the excessive stresses by suitably controlling the turbine, thus decreasing the COE value. Thus, by the above online COE determination 136, the optimum operating level with the lowest possible COE values can be obtained for the current local and meteorological conditions by use of a simple control loop. On this optimum operating level, if the COE values are higher than the maximum allowable COE 118 value determined by the economy model 126, the turbine will be brought to a standstill until more favorable conditions occur (e.g. lower turbulences or lower wind velocity). Thus, during low turbulences, the turbines can supply power still in case of much higher wind velocities than had been possible in the state of the art.

As a further possible component, schematically illustrated in the right-hand edge region of the drawing to the right of the vertical dash-dotted line, a short-time control unit 140 may be provided for reduction of temporary loading peaks. The input data of said unit 140 include loading data 142 and optionally also wind field 114 data, which other than in the operating level control unit 125 -are not evaluated statistically but subjected to a current value analysis; in a signal processing model 144 also referred to as a loading prognosis, predictions can thus be made on loading peaks which will be reduced by the short-time control unit 140 through limitation the pitch angle 105 or the rotor speed 106.

Therefore, particularly when using of data of neighboring wind power plants 116 located upstream relative to the wind direction, the loading of the plant and thus also the current COE value 112 during wind velocities above the nominal wind are massively reduced; notably, turbines located behind other turbines in the wind direction can react exactly and with a suitable delay on wind occurrences which have been registered in the turbine arranged upstream. Thus, the unavoidable disadvantages (trailing turbulences) for the following turbines can be compensated for.

For guaranteeing that the available potential of the plant will not be reduced in case of a possible failure of one component of the above control system, the operating control system should preferably be designed such that the standard control system illustrated on the left: side of the drawing is separated, under the

hardware aspect, from the other components of the operating level control unit 128.

a' conceded Thus, should the operating level control unit 128 be not available, the turbine will nonetheless remain connected to the grid, even though it will then be subjected to the power limitation for high wind velocities as provided by the state of the art.

The described control strategy is by no means limited to the illustrated embodiment for a variable-speed pitch plant but is in its essence also useful for pitch plants designed for fixed speeds or pole reversal, or for stall or active stall plants.

Further, a large number of specific details and refinements of the system can be contemplated (additional measurement values, damage modules for further components of the plant etc.), all of them following the basic idea of determining the optimum operating time under the current local and meteorological conditions.

Please replace the Abstract paragraph on page 15 with the following paragraph.

ABSTRACT OF THE DISCLOSURE

a2

A control system for a wind power plant that includes a damage module and a control module. The damage module compares existing stress conditions on one or more component parts of the wind power plant to current energy generating costs. The control module alters electric power generated by the wind power plant based upon the comparison.

IN THE CLAIMS

Presented below are the amended claims in a clean-unmarked format. Please add claims 14-33. Please cancel claims 1-13 without prejudice.

a³
14. (New) A control system for a wind power plant, comprising:

a damage module operable to compare existing stress conditions on one or more component parts of the wind power plant to current energy generating costs; and

a control module operable to alter electric power generated by the wind power plant based upon the comparison.

15. (New) The control system of claim 14, further comprising:

a cost of energy module operable to provide the current energy generating costs based upon financing data for the wind power plant and current charges for power supply.

16. (New) The control system of claim 14, further comprising:

a stress module operable to determine existing stress conditions on one or more component parts of the wind power plant and to provide data on existing stress conditions on the one or more component parts of the wind power plant to the damage module.

a 3
Cmt.

17. (New) The control system of claim 16, wherein the stress module compares existing stress on a first component to designed allowable stresses to provide the stress data to the damage module.

18. (New) The control system of claim 16, wherein the stress module determines existing stress conditions on a first component based upon local meteorological conditions.

19. (New) The control system of claim 14, wherein the control module changes blade pitch of one or more turbine blades of the wind power plant to alter the electrical power generated by the wind power plant.

20. (New) The control system of claim 19, wherein change to the blade pitch occurs in a direction of a feathered pitch.

21. (New) The control system of claim 14, wherein the control module alters rotor speed of the wind power plant to alter the electrical power generated by the wind power plant.

22. (New) The control system of claim 14, further comprising:

a3
cmt.

a second control module to anticipatorily reduce loading of the wind power plant based upon receiving data of neighboring wind power plants located upstream relative to a wind direction.

23. (New) The control system of claim 14, wherein the damage module determines the damage to the one or more components based upon actual spectra.

24. (New) A method, comprising:

comparing existing stress conditions on one or more component parts of a wind power plant based upon local meteorological conditions to energy generating costs at that time; and

controlling blade pitch of one or more turbine blades of the wind power plant based upon the comparison.

25. (New) The method of claim 24, further comprising:

detecting a direction of a wind; and

anticipatorily reducing loading of the wind power plant based upon receiving data from one or more neighboring wind power plants located upstream relative to the direction of the wind.

26. (New) The method of claim 24, further comprising:

a3
cont.

determining the energy generating costs at that time based upon financing data for the wind power plant and current charges for power supply.

27. (New) The method of claim 24, further comprising:

determining the existing stress on a first component by measuring stretching on representative points along the first component as well as factoring in how long the first component has been in service.

28. (New) The method of claim 24, further comprising:

determining the existing stress on a first component by measuring deformation in elastic bearings.

29. (New) An apparatus, comprising:

means for comparing existing stress conditions on one or more component parts of a wind power plant based upon local meteorological conditions to energy generating costs at that time; and

means for controlling blade pitch of one or more turbine blades of the wind power plant based upon the comparison.

30. (New) The apparatus of claim 29, further comprising:

a3
cancel.

means for controlling rotor speed of the wind power plant to alter electrical power generated by the wind power plant.

31. (New) The apparatus of claim 29, further comprising:

means for detecting a direction of a wind; and

means for anticipatorily reducing loading of the wind power plant based upon receiving data from one or more neighboring wind power plants located upstream relative to the direction of the wind.

32. (New) The method of claim 29, further comprising:

means for determining the energy generating costs at that time based upon financing data for the wind power plant and current charges for power supply.

33. (New) The method of claim 29, further comprising:

means for determining the existing stress on a first component by measuring stretching on representative points along the first component as well as factoring in how long the first component has been in service.

REMARKS

Applicant respectfully requests reconsideration of this application as amended. The language used in the Abstract paragraph stands objected to. Claims 1-13 stand rejected under 35 U.S.C. 112, first paragraph, as containing subject matter, which was not in the drawings and not described in the specification. Claims 1-13 stand rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention. Claims 1, 5, and 7-13 stand rejected under 35 U.S.C. 102(b) as being anticipated by United States Patent No. 4,155,252 by Morrill (hereinafter Morrill). Claims 1, 4, 5, and 7 stand rejected under 35 U.S.C. 102(b) as being anticipated by United States Patent No. 4,695,736 by Doman et al. (hereinafter Doman). Claims 1 and 6 stand rejected under 35 U.S.C. 102(b) as being anticipated by United States Patent No. 4,420,692 by Kos et al (hereinafter Kos). Claim 2 stands rejected under 35 U.S.C. 103(a) as being unpatentable over Morrill in view of United States Patent No. 4,160,170 by Harner (hereinafter Harner). Claims 1-13 are pending in the application. Claims 14-33 have been added. Claims 1-13 have been canceled without prejudice. Amended Pages 2-11, the Abstract Paragraph, and substitute Figure 1 have been submitted. Applicants respectfully request the Examiner to accept the three-month extension submitted with this response.

The language used in the Abstract paragraph stands objected to. The Examiner states "The form and legal phraseology often used in patent claims, such as "means" and "said," should be avoided." (Office Action, Page 3). Applicant

respectfully submits a new Abstract paragraph that does not contain the objectionable legal phraseology.

Claims 1-13 stand rejected under 35 U.S.C. 112, first paragraph, as containing subject matter, which was not in the drawings and not described in the specification. Applicant cancels claims 1-13 without prejudice and without any admission that claims 1-13 contained subject matter, which was not in the drawings and not described in the specification. Applicant respectfully submits amended specification pages 2-11 and substitute Figure 1 with corresponding reference numbers. Applicant respectfully submits that claims 14-33 are supported throughout the specification; however, applicant directs the examiner to substitute Figure 1 and amended pages 5-11 for such support.

Claims 1-13 stand rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention. Applicant cancels claims 1-13 without prejudice and without any admission that claims 1-13 failed to particularly point out and distinctly claim the subject matter which applicant regards as the invention. Applicant respectfully submits that new claims 14-33 contain no new matter. Applicant respectfully submit that claims 14-33 are supported throughout the specification, however, applicant directs the examiner to substitute Figure 1 and amended pages 5-11 for such support.

Claims 1, 5, and 7-13 stand rejected under 35 U.S.C. 102(b) as being anticipated by Morrill. Applicant cancels claims 1-13 without prejudice.

Applicant respectfully submits that new claim 14 patentably distinguishes over Morrill because Morrill fails to disclose one or more limitations recited in claim 14. Morrill discloses, "A system for detecting and metering wind energy and recording the total integrated energy or power levels over any desired period of time." (Morrill, Abstract Paragraph). However, Claim 14 recites:

14. A control system for a wind power plant, comprising:
a damage module operable to compare existing stress conditions on one or more component parts of the wind power plant to current energy generating costs; and
a control module operable to alter electric power generated by the wind power plant based upon the comparison. (Emphasis added).

Morrill merely discloses a recorder to record wind energy and does not alter the electric power generated by the wind power plant.

Therefore new claim 14 patentably distinguishes over Morrill. Dependant claims 15-23 depend upon and include the limitations of independent claim 14. Therefore, dependent claims 15-23 patentably distinguish over the cited art because Morrill does not disclose these limitations recited in claim 14.

Independent Claim 24 recites:

24. A method, comprising:
comparing existing stress conditions on one or more component parts of a wind power plant based upon local meteorological conditions to energy generating costs at that time; and
controlling blade pitch of one or more turbine blades of the wind power plant based upon the comparison. (Emphasis added).

Morrill merely discloses a recorder to record wind energy and does not control the blade pitch of one or more turbine blades of the wind power plant.

Therefore new claim 24 patentably distinguishes over Morrill. Dependant claims 25-28 depend upon and include the limitations of independent claim 24. Therefore, dependent claims 25-28 patentably distinguish over the cited art because Morrill does not disclose these limitations recited in claim 24.

Similarly, independent Claim 29 recites:

29. An apparatus, comprising:

means for comparing existing stress conditions on one or more component parts of a wind power plant based upon local meteorological conditions to energy generating costs at that time; and

means for controlling blade pitch of one or more turbine blades of the wind power plant based upon the comparison. (Emphasis added).

Morrill merely discloses a recorder to record wind energy and does not control the blade pitch of one or more turbine blades of the wind power plant.

Therefore new claim 29 patentably distinguishes over Morrill. Dependant claims 30-33 depend upon and include the limitations of independent claim 29. Therefore, dependent claims 30-33 patentably distinguish over the cited art because Morrill does not disclose these limitations recited in claim 29.

Claims 1, 4, 5, and 7 stand rejected under 35 U.S.C. 102(b) as being anticipated by Doman. Applicant cancels claims 1-13 without prejudice.

Applicant respectfully submits that new claim 14 patentably distinguishes over Doman because Doman fails to disclose one or more limitations recited in claim 14. Doman discloses:

The variable speed wind turbine controller includes a speed maneuvering controller responsive to the sensed power signal for providing a speed reference signal that is compared to the sensed generator speed signal. A difference signal indicative of the difference between the speed reference signal and the sensed generator speed signal is integrated to provide the generator torque command signal for the frequency converter. (Doman, Col. 2, Lns. 11-19) (Emphasis added)

Doman discloses a control system but does not compare existing stress conditions to generating costs at that time to alter electric power generated by the wind power plant. Rather, Doman compares a speed reference signal to the sensed generator speed signal to provide the generator torque command signal.

Therefore new claim 14 patentably distinguishes over Doman. Dependant claims 15-23 depend upon and include the limitations of independent claim 14. Therefore, dependent claims 15-23 patentably distinguish over the cited art because Doman does not disclose these limitations recited in claim 14.

Applicant respectfully submits that new claim 24 patentably distinguishes over Doman because Doman fails to disclose one or more limitations recited in claim 24.

Doman discloses a control system but does not compare existing stress conditions to generating costs at that time to control the blade pitch of one or more turbine blades of the wind power plant. Rather, Doman compares a speed reference signal to the sensed generator speed signal to provide the generator torque command signal.

Therefore new claim 24 patentably distinguishes over Doman. Dependant claims 25-28 depend upon and include the limitations of independent claim 24.

Therefore, dependent claims 25-28 patentably distinguish over the cited art because Doman does not disclose these limitations recited in claim 24.

Similarly, Applicant respectfully submits that new claim 29 patentably distinguishes over Doman because Doman fails to disclose one or more limitations recited in claim 29.

Doman discloses a control system but does not compare existing stress conditions to generating costs at that time to control the blade pitch of one or more turbine blades of the wind power plant.

Therefore new claim 29 patentably distinguishes over Doman. Dependent claims 30-33 depend upon and include the limitations of independent claim 29. Therefore, dependent claims 30-33 patentably distinguish over the cited art because Doman does not disclose these limitations recited in claim 29.

Claims 1 and 6 stand rejected under 35 U.S.C. 102(b) as being anticipated by Kos. Applicant cancels claims 1-13 without prejudice.

Applicant respectfully submits that new claim 14 patentably distinguishes over Kos because Kos fails to disclose one or more limitations recited in claim 14.

Kos discloses:

Motion responsive wind turbine tower damping system having an accelerometer (1) disposed on the support tower (12) of a wind turbine electric generating system in the vicinity of the rotor (10, 16) thereof provides a signal (1) indicative of acceleration of the tower in the direction of the rotor rotational axis. The signal (2) is passed through a band-pass filter (4) for summation (9) with a torque/power controlled (100) blade pitch angle reference rate signal (98), the integral (104) of which provides a blade pitch angle reference signal (40) to control the pitch angle of the rotor blades (10) through a pitch change mechanism

(38), thereby to provide additional, positive aerodynamic damping to the tower while modulating blade angle for constant torque/power in response to wind turbulence. (Kos, Abstract Paragraph) (Emphasis added).

Kos discloses a control system but does not compare existing stress conditions to generating costs at that time to alter electric power generated by the wind power plant. Rather, Kos integrates an acceleration signal with a blade pitch angle reference rate signal to control the pitch angle of the rotor blades.

Therefore new claim 14 patentably distinguishes over Kos. Dependant claims 15-23 depend upon and include the limitations of independent claim 14. Therefore, dependent claims 15-23 patentably distinguish over the cited art because Kos does not disclose these limitations recited in claim 14.

Applicant respectfully submits that new claim 24 patentably distinguishes over Kos because Kos fails to disclose one or more limitations recited in claim 24

Kos discloses a control system but does not compare existing stress conditions to generating costs at that time to control the blade pitch of one or more turbine blades of the wind power plant. Rather, Kos integrates an acceleration signal with a blade pitch angle reference rate signal to control the pitch angle of the rotor blades.

Therefore new claim 24 patentably distinguishes over Kos. Dependant claims 25-28 depend upon and include the limitations of independent claim 24. Therefore, dependent claims 25-28 patentably distinguish over the cited art because Kos does not disclose these limitations recited in claim 24.

Similarly, Applicant respectfully submits that new claim 29 patentably distinguishes over Kos because Kos fails to disclose one or more limitations recited in claim 29.

Kos discloses a control system but does not compare existing stress conditions to generating costs at that time to control the blade pitch of one or more turbine blades of the wind power plant.

Therefore new claim 29 patentably distinguishes over Kos. Dependant claims 30-33 depend upon and include the limitations of independent claim 29. Therefore, dependent claims 30-33 patentably distinguish over the cited art because Kos does not disclose these limitations recited in claim 29.

Claim 2 stands rejected under 35 U.S.C. 103(a) as being unpatentable over Morrill in view of Harner. Applicant canceled claim 2 without prejudice.

Applicant respectfully submits that new claim 14 patentably distinguishes Morrill in view of Harner because the combination of Morrill and Harner fails to disclose one or more limitations recited in claim 14. As discussed above, Morrill merely discloses a recorder to record wind energy and does not alter the electric power generated by the wind power plant. Harner discloses:

The pitch angle of the wind turbine blades is controlled in a closed loop manner to maintain either a constant generator speed for isolated power generating stations or when the generator is synchronized to the load, or constant generator output power or shaft torque when the generator is connected to an electrical grid. Open loop acceleration and deceleration schedules are provided to minimize blade stress and shaft torque variations during start up and shutdown transients, limiting blade angle excursions as a function of wind velocity and speed. The schedules may be implemented either electronically or by a suitably programmed digital

computer. The gains in the speed, torque and power loop controls are scheduled as a function of average wind velocity to optimize stability and response. An anticipatory blade angle schedule responsive to instantaneous wind velocity is added to the desired blade angle reference from the closed loop controls to minimize transient excursions in output power or generator speed resulting from wind gusts. (Harner, Abstract Paragraph) (Emphasis added).

Harner discloses a control system but does not compare existing stress conditions to generating costs at that time to alter electric power generated by the wind power plant. Rather, Harner teaches scheduling gains in the speed, torque and power loop controls as a function of average wind velocity to control blade pitch and output power.

Therefore new claim 14 patentably distinguishes over Morrill in view of Harner. Dependant claims 15-23 depend upon and include the limitations of independent claim 14. Therefore, dependent claims 15-23 patentably distinguish over the cited art because the combination of Morrill and Harner does not disclose these limitations recited in claim 14.

Applicant respectfully submits that new claim 24 patentably distinguishes over Morrill in view of Harner because the combination of Morrill and Harner fails to disclose one or more limitations recited in claim 24

Harner discloses a control system but does not compare existing stress conditions to generating costs at that time to control the blade pitch of one or more turbine blades of the wind power plant. Rather, Harner teaches scheduling gains in the speed, torque and power loop controls as a function of average wind velocity to control blade pitch.

Therefore new claim 24 patentably distinguishes over Morrill in view of Harner. Dependant claims 25-28 depend upon and include the limitations of independent claim 24. Therefore, dependent claims 25-28 patentably distinguish over the cited art because the combination of Morrill and Harner does not disclose these limitations recited in claim 24.

Similarly, Applicant respectfully submits that new claim 29 patentably distinguishes over Morrill in view of Harner because the combination of Morrill and Harner fails to disclose one or more limitations recited in claim 29.

Harner discloses a control system but does not compare existing stress conditions to generating costs at that time to control the blade pitch of one or more turbine blades of the wind power plant.

Therefore new claim 29 patentably distinguishes over Morrill in view of Harner. Dependant claims 30-33 depend upon and include the limitations of independent claim 29. Therefore, dependent claims 30-33 patentably distinguish over the cited art because the combination of Morrill and Harner does not disclose these limitations recited in claim 29.

Applicant submits a certified copy of the German application to fulfill priority requirements.


Accordingly, Applicant respectfully submits that the rejections under 35 U.S.C. § 112, § 102, and § 103 have been overcome by the amendments and the remarks and withdrawal of these rejections is respectfully requested. Applicant

submits that new Claims 14-33 are in condition for allowance and such action is earnestly solicited.

Please charge any shortages and credit any overcharges to our Deposit
Account No. 02-2666.

Respectfully submitted,
BLAKELY, SOKOLOFF, TAYLOR &
ZAFMAN LLP

Dated: 10-30, 2002



Thomas S. Ferrill
Attorney for Applicant
Registration No. 42,532

12400 Wilshire Boulevard
Seventh Floor
Los Angeles, CA 90025-1026
(408) 720-8598